



(19)

(11) Publication number:

08109043 A

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **06266174**(51) Intl. Cl.: **C03C 17/34 C03C 17/25 G06F 3/033 H01B 5/14**(22) Application date: **05.10.94**

(30) Priority:

(43) Date of application publication: **30.04.96**

(84) Designated contracting states:

(71) Applicant: **NIPPON SODA CO LTD**(72) Inventor: **SAITO KAZUNORI
SETA YASUHIRO
TAKIZAWA KAZUMASA**

(74) Representative:

**(54) TRANSPARENT
ELECTROCONDUCTIVE
FILM-ATTACHED GLASS
HAVING HIGH RESISTANCE**

(57) Abstract:

PURPOSE: To obtain transparent electroconductive film-attached glass having high resistance and excellent in uniformity by forming a film of silicon dioxide onto a glass substrate and forming a transparent electroconductive film thereon to provide a film having two layer

structure.

CONSTITUTION: Silicon dioxide film containing phosphorus in an amount of 0.01-10wt.% and/or boron in an amount of 0.01-10wt.% based on silicon dioxide is formed on a transparent glass substrate in a film thickness of 60-150nm. A transparent electroconductive film having 1.7-2.2 refractive index, 200-3000 Ω /square and \pm 2% linearity value is formed in a film thickness of 10-30nm thereon to provide the objective transparent electroconductive film attached glass. ITO, FTO, ATO, etc., is used as the transparent electroconductive film and silicon dioxide is formed into a film by a sputtering method, a CVD method, a spraying method, etc.

COPYRIGHT: (C)1996,JPO